



# **TEST REPORT:                    HVG-240-30**

## **240W Constant Voltage + Constant Current LED Driver**

### **■ DESIGN VERIFY TEST**

Output Function Test

Input Function Test

Protection Function Test

Control Function Test

Component Stress Test

### **■ SAFETY & E.M.C. TEST**

Safety Test

E.M.C. Test


### **■ RELIABILITY TEST**

ENVIRONMENT TEST

DESIGN VERIFY TEST  
OUTPUT FUNCTION TEST


NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	OUTPUT VOLTAGE ADJUST RANGE	CH1: 28.00V ~ 32.00V	I/P : 347VAC O/P: MIN LOAD TA : 25°C	CH1: 25.87V ~ 32.98V
2	CONSTANT CURRENT REGION	CH1: 15V ~ 30V	I/P : 347VAC O/P: FULL LOAD TA : 25°C	CH1: 0.22V ~ 30V
3	CURRENT ADJ. RANGE	CH1: 4A ~ 8A	I/P : 347VAC I/P : 230VAC O/P: CV MIN& CV MAX-1V TA : 25°C	2.64A ~ 8.51A 347VAC-CV MAX-1V 2.57A ~ 8.41A 347VAC-CV MIN 2.65A ~ 8.52A 230VAC-CV MAX-1V 2.6A ~ 8.42A 347VAC-CV MIN
4	OUTPUT VOLTAGE TOLERANCE (Max)	V1 : 1.0% ~ -1.0%	I/P : 180VAC / 528VAC O/P: FULL / MINLOAD TA= 25°C	V1: 0.12% ~ -0.12%
5	LINE REGULATION (MAX.)	V1 : 0.5% ~ -0.5%	I/P : 180VAC / 528VAC O/P: FULL LOAD TA : 25°C	V1: 0.00% ~ 0.00%
6	LOAD REGULATION (MAX.)	V1 : 0.5% ~ -0.5%	I/P : 347VAC O/P: MIN LOAD ~ FULL LOAD TA : 25°C	V1: 0.10% ~ -0.13%
7	OVER/UNDERSHOOT TEST	< ±5%	I/P : 347VAC O/P: FULL LOAD TA : 25°C	TEST < ±5%
	RIPPLE & NOISE(Max)	V1 : 200 mVp-p	I/P : 347VAC O/P: FULL LOAD TA : 25°C	V1 : 46.4 mVp-p

low frequency :




SET UP TIME (MAX.)	347VAC : 400ms	I/P : 347VAC	347VAC: 296ms
	230VAC : 500ms	I/P : 230VAC	230VAC: 312ms
	480VAC : 400ms	I/P : 480VAC	480VAC: 306ms
		O/P: FULL LOAD TA : 25°C	


INPUT=230VAC/50HZ @ FULL LOAD  
CH1 : Output Voltage CH2 : AC Input Voltage




INPUT=347VAC/60HZ @ FULL LOAD  
CH1 : Output Voltage CH2 : AC Input Voltage




RISE TIME (MAX.)	347VAC : 150ms	I/P : 347VAC	347VAC: 30.2ms
	230VAC : 150ms	I/P : 230VAC	230VAC: 29.4ms
	480VAC : 150ms	I/P : 480VAC	480VAC: 27.2ms
		O/P: FULL LOAD	
		TA : 25°C	



HOLD UP TIME (TYP.)	347VAC : 12ms	I/P : 347VAC	347VAC: 23.2ms
	480VAC : 12ms	I/P : 480VAC	480VAC: 16.8ms
		O/P: FULL LOAD	
		TA : 25°C	




DYNAMIC LOAD	V1 : 3000 mVp-p	I/P : 347VAC	(1).	(2).	unit:mVp-p
		O/P:	198mv	170mv	
		(1)Full/Min load 50%duty/120HZ			
		(2)Full/Min load 50%duty/1KHZ			
		TA : 25°C			




## INPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT																																																							
1	INPUT VOLTAGE RANGE	180VAC ~ 528VAC	I/P : TESTING O/P : FULL LOAD Ta : 25°C I/P : LOW-LINE = 177VAC HIGH-LINE = 538VAC O/P : FULL/MIN LOAD ON:30 Sec ; OFF:30 Sec 10MIN ( POWER ON/OFF NO DAMAGE )	136.0VAC ~ 528VAC  TEST : OK																																																							
2	INPUT FREQUENCY RANGE	47HZ ~ 63HZ NO DAMAGE	I/P : 180VAC ~ 528VAC O/P : FULL-MIN LOAD Ta : 25°C	TEST : OK																																																							
3	INPUT CURRENT (TYP.)	0.8 / 347VAC 0.6 / 480VAC	I/P : 347VAC I/P : 480VAC O/P : FULL LOAD TA : 25°C	I= 0.7812 / 347VAC I= 0.5635 / 480VAC																																																							
4	LEAKAGE CURRENT	< 0.75mA	I/P : 480VAC O/P : MIN LOAD TA : 25°C	L-FG: 0.32 mA N-FG: 0.31 mA																																																							
5	POWER FACTOR (TYP.)	0.95 / 347VAC	I/P : 347VAC	PF= 0.9808 / 347VAC																																																							
		0.93 / 480VAC	I/P : 480VAC	PF= 0.9514 / 480VAC																																																							
		0.97 / 277VAC	I/P : 277VAC	PF= 0.9895 / 277VAC																																																							
		0.98 / 230VAC	I/P : 230VAC	PF= 0.9913 / 230VAC																																																							
			O/P: FULL LOAD TA : 25°C																																																								
<table border="1"> <caption>Power Factor vs Load Data</caption> <thead> <tr> <th>Load (%)</th> <th>230VAC</th> <th>277VAC</th> <th>347VAC</th> <th>480VAC</th> </tr> </thead> <tbody> <tr><td>10%</td><td>0.87</td><td>0.82</td><td>0.70</td><td>0.58</td></tr> <tr><td>20%</td><td>0.94</td><td>0.92</td><td>0.85</td><td>0.68</td></tr> <tr><td>30%</td><td>0.96</td><td>0.95</td><td>0.92</td><td>0.78</td></tr> <tr><td>40%</td><td>0.97</td><td>0.96</td><td>0.94</td><td>0.85</td></tr> <tr><td>50%</td><td>0.98</td><td>0.97</td><td>0.96</td><td>0.89</td></tr> <tr><td>60%</td><td>0.98</td><td>0.97</td><td>0.97</td><td>0.92</td></tr> <tr><td>70%</td><td>0.98</td><td>0.97</td><td>0.97</td><td>0.94</td></tr> <tr><td>80%</td><td>0.98</td><td>0.97</td><td>0.97</td><td>0.95</td></tr> <tr><td>90%</td><td>0.98</td><td>0.97</td><td>0.97</td><td>0.95</td></tr> <tr><td>100%</td><td>0.98</td><td>0.97</td><td>0.97</td><td>0.95</td></tr> </tbody> </table>					Load (%)	230VAC	277VAC	347VAC	480VAC	10%	0.87	0.82	0.70	0.58	20%	0.94	0.92	0.85	0.68	30%	0.96	0.95	0.92	0.78	40%	0.97	0.96	0.94	0.85	50%	0.98	0.97	0.96	0.89	60%	0.98	0.97	0.97	0.92	70%	0.98	0.97	0.97	0.94	80%	0.98	0.97	0.97	0.95	90%	0.98	0.97	0.97	0.95	100%	0.98	0.97	0.97	0.95
Load (%)	230VAC	277VAC	347VAC	480VAC																																																							
10%	0.87	0.82	0.70	0.58																																																							
20%	0.94	0.92	0.85	0.68																																																							
30%	0.96	0.95	0.92	0.78																																																							
40%	0.97	0.96	0.94	0.85																																																							
50%	0.98	0.97	0.96	0.89																																																							
60%	0.98	0.97	0.97	0.92																																																							
70%	0.98	0.97	0.97	0.94																																																							
80%	0.98	0.97	0.97	0.95																																																							
90%	0.98	0.97	0.97	0.95																																																							
100%	0.98	0.97	0.97	0.95																																																							
	EFFICIENCY (TYP.)	92.5%	I/P : 347VAC O/P: FULL LOAD TA : 25°C	93 %																																																							




6

TOTAL HARMONIC DISTORTION	Total harmonic distortion will be lower than 20% when output loading is 50% or higher at 230VAC / 277VAC / 347VAC / 480VAC	I/P : 347VAC / 50% LOAD I/P : 480VAC / 60% LOAD TA : 25°C	THD : 14.136 / 347VAC THD : 14 / 480VAC
---------------------------	--	---	--



7

INRUSH CURRENT (TYP.)	50A / 480VAC width= 532 us measured at 50% Ipeak COLD START	I/P : 480VAC O/P : FULL LOAD TA : 25°C	I= 41.3 / 480VAC T50= 540 us
-----------------------	---	--	---------------------------------



8

### PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	OVER LOAD PROTECTION	95% ~ 108%	I/P: 528VAC I/P: 180VAC O/P: TESTING TA: 25°C	102.3% /528VAC 102.2% /180 VAC Constant Current Limiting

2	OVER VOLTAGE PROTECTION	33.00V ~ 39.00V	I/P: 528VAC I/P: 180VAC O/P: MIN LOAD TA: 25°C	36V 36.5V Shut down Re- power ON
3	OVER TEMPERATURE PROTECTION	Shut down Re- power ON	I/P: 347VAC O/P: FULL LOAD	O.T.P. Active Shut down Re- power ON
4	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P: 528VAC O/P: FULL LOAD Ta: 25°C	NO DAMAGE Constant Current Limiting

### COMPONENT STRESS TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	PWM Power Transistor	Q901 Rated : 950V 9.0A	I/P : 531VAC I/P : 177VAC VDS : O/P : (1)Full Load Turn on (2) Output Short (3)Full load continue (4)Dynamic Load Full/Min Load 90%Duty/1KHz (5)Dynamic Load Full/Min Load 90%Duty/5KHz (6)Dynamic Load Full/Min Load 50%Duty/120Hz (7)0%→400% Load  Ta : 25°C	VIN: 531VAC 177VAC VDS: VDS: (1). 879.0V 847.0V (2). 879.0V 871.0V (3). 799.0V 807.0V (4). 863.0V 863.0V (5). 871.0V 855.0V (6). 863.0V 855.0V (7). 879.0V 863.0V
2	O/P Diode (MOSFET)	Q101 Rated : 100V 80.0A Q102 Rated : 100V 80.0A	I/P : 531VAC VDS : O/P : (1)Full Load Turn on (2) Output Short (3)Full load continue (4)Dynamic Load Full/Min Load 90%Duty/1KHz (5)Dynamic Load Full/Min Load 90%Duty/5KHz (6)Dynamic Load Full/Min Load 50%Duty/120Hz (7)0%→400% Load (8) NO LOAD  Ta : 25°C	Q101 Q102 VDS : VDS : (1). 67.1V 68.6V (2). 13.1V 11.7V (3). 67.0V 67.9V (4). 67.8V 68.7V (5). 67.8V 68.7V (6). 67.0V 67.9V (7). 65.4V 69.5V (8). 65.4V 67.1V
3	Input Capacitor	C5 Rated : 82uf 450V	I/P : 531VAC O/P : (1)Full Load Turn on /Off (2)Min load Turn on /Off (3)Full Load /Min load Change  Ta : 25°C	C5 (1). 382.0V (2). 431.0V (3). 411.0V
4	Control IC	U1 Rated : 20V (max) 10V (min)	I/P : 531VAC O/P : (1)Full Load (2)Output Short (3)O.L.P (4)O.V.P (5)Low Line No Load Vo(min)  Ta : 25°C	U1 (1). 15.3V (2). 13.3V (3). 13.3V (4). 15.3V (5). 11.9V
5	PFC Power Transistor	Q1 Rated : 1050V 9.0A	I/P : 531VAC VDS : O/P : (1)Full Load Turn on (2) Output Short (3)Full load continue (4)Dynamic Load Full/Min Load 90%Duty/1KHz (5)Dynamic Load Full/Min Load 90%Duty/5KHz (6)Dynamic Load Full/Min Load 50%Duty/120Hz (7)0%→400% Load  Ta : 25°C	VIN: 531VAC VDS: (1). 847.0V (2). 911.0V (3). 823.0V (4). 871.0V (5). 887.0V (6). 911.0V (7). 855.0V

### SAFETY & E.M.C. TEST SAFETY TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
----	-----------	---------------	----------------	--------

1	WITHSTAND VOLTAGE	I/P-O/P : 3.75KVAC /min I/P-FG : 2.0KVAC /min O/P-FG : 1.5KVAC /min	I/P-O/P: 4.13KVAC /min I/P-FG: 2.40KVAC /min O/P-FG: 1.80KVAC /min Ta : 25°C	I/P-O/P: 1.88mA I/P-FG: 1.9mA O/P-FG: 1.0mA NO DAMAGE
2	ISOLATION RESISTANCE	I/P-O/P : 500VDC>100MΩ I/P-FG : 500VDC>100MΩ O/P-FG : 500VDC>100MΩ	I/P-O/P: 500VDC I/P-FG: 500VDC O/P-FG: 500VDC Ta : 25°C/70%RH	I/P-O/P: 10.3GΩ I/P-FG: 3.8GΩ O/P-FG: 14.4GΩ NO DAMAGE
2	GROUNDING CONTINUITY	FG(PE) TO CHASSIS OR TRACE < 100 mΩ	40 A / 2min Ta : 25°C/70%RH	26 mΩ

### E.M.C. TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	CONDUCTION	EN55022 CLASS B	I/P : 347 VAC/50HZ O/P : FULL LOAD / 50% LOAD Ta : 25°C	PASS Test by certified Lab
2	CONDUCTION	EN55022 CLASS B	I/P : 347 VAC/50HZ O/P : FULL LOAD Ta : 25°C	PASS Test by certified Lab
3	E.S.D	EN61000-4-2 LIGHT INDUSTRY AIR : 8KV / Contact : 4KV	I/P : 347 VAC/50HZ O/P : FULL LOAD Ta : 25°C	CRITERIA A
4	E.F.T	EN61000-4-4 LIGHT INDUSTRY INPUT : 1KV	I/P : 347 VAC/50HZ O/P : FULL LOAD Ta : 25°C	CRITERIA A
5	SURGE	IEC61000-4-5 INDUSTRY L-N : 2KV;L/N-PE : 4KV	I/P : 347 VAC/50HZ O/P : FULL LOAD Ta : 25°C	CRITERIA A

### RELIABILITY TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT																																																																												
1	TEMPERATURE RISE TEST	MODEL : HVG-240-24 1. ROOM AMBIENT BURN-IN : 3.0hrs IP: 230VAC O/P: 100% LOAD TA= 24.8°C 2. HIGH AMBIENT BURN-IN : 2.0hrs IP: 230VAC O/P: 100% LOAD TA= 59.2°C	<table border="1"> <thead> <tr> <th>CH.</th> <th>Position</th> <th>ROOM AMBIENT Ta= 24.8°C</th> <th>HIGH AMBIENT Ta= 59.2°C</th> </tr> </thead> <tbody> <tr><td>1</td><td>BD1</td><td>62.0°C</td><td>93.3°C</td></tr> <tr><td>2</td><td>Q1</td><td>62.5°C</td><td>94.5°C</td></tr> <tr><td>3</td><td>Q901</td><td>63.9°C</td><td>96.4°C</td></tr> <tr><td>4</td><td>L2</td><td>60.7°C</td><td>91.6°C</td></tr> <tr><td>5</td><td>C2</td><td>58.9°C</td><td>88.5°C</td></tr> <tr><td>6</td><td>C10</td><td>61.3°C</td><td>92.9°C</td></tr> <tr><td>7</td><td>L1</td><td>64.2°C</td><td>97.1°C</td></tr> <tr><td>8</td><td>ZNR2</td><td>76.4°C</td><td>103.3°C</td></tr> <tr><td>9</td><td>RTH3</td><td>58.8°C</td><td>90.5°C</td></tr> <tr><td>10</td><td>T1</td><td>68.5°C</td><td>103.7°C</td></tr> <tr><td>11</td><td>C46</td><td>62.0°C</td><td>93.8°C</td></tr> <tr><td>12</td><td>C54</td><td>60.6°C</td><td>92.1°C</td></tr> <tr><td>13</td><td>Q102</td><td>62.0°C</td><td>94.8°C</td></tr> <tr><td>14</td><td>C102</td><td>59.6°C</td><td>91.8°C</td></tr> <tr><td>15</td><td>C201</td><td>63.0°C</td><td>94.5°C</td></tr> <tr><td>16</td><td>C200</td><td>61.7°C</td><td>93.6°C</td></tr> <tr><td>17</td><td>U1</td><td>63.6°C</td><td>95.2°C</td></tr> <tr><td>20</td><td>C5</td><td>61.9°C</td><td>93.4°C</td></tr> </tbody> </table>	CH.	Position	ROOM AMBIENT Ta= 24.8°C	HIGH AMBIENT Ta= 59.2°C	1	BD1	62.0°C	93.3°C	2	Q1	62.5°C	94.5°C	3	Q901	63.9°C	96.4°C	4	L2	60.7°C	91.6°C	5	C2	58.9°C	88.5°C	6	C10	61.3°C	92.9°C	7	L1	64.2°C	97.1°C	8	ZNR2	76.4°C	103.3°C	9	RTH3	58.8°C	90.5°C	10	T1	68.5°C	103.7°C	11	C46	62.0°C	93.8°C	12	C54	60.6°C	92.1°C	13	Q102	62.0°C	94.8°C	14	C102	59.6°C	91.8°C	15	C201	63.0°C	94.5°C	16	C200	61.7°C	93.6°C	17	U1	63.6°C	95.2°C	20	C5	61.9°C	93.4°C	
CH.	Position	ROOM AMBIENT Ta= 24.8°C	HIGH AMBIENT Ta= 59.2°C																																																																													
1	BD1	62.0°C	93.3°C																																																																													
2	Q1	62.5°C	94.5°C																																																																													
3	Q901	63.9°C	96.4°C																																																																													
4	L2	60.7°C	91.6°C																																																																													
5	C2	58.9°C	88.5°C																																																																													
6	C10	61.3°C	92.9°C																																																																													
7	L1	64.2°C	97.1°C																																																																													
8	ZNR2	76.4°C	103.3°C																																																																													
9	RTH3	58.8°C	90.5°C																																																																													
10	T1	68.5°C	103.7°C																																																																													
11	C46	62.0°C	93.8°C																																																																													
12	C54	60.6°C	92.1°C																																																																													
13	Q102	62.0°C	94.8°C																																																																													
14	C102	59.6°C	91.8°C																																																																													
15	C201	63.0°C	94.5°C																																																																													
16	C200	61.7°C	93.6°C																																																																													
17	U1	63.6°C	95.2°C																																																																													
20	C5	61.9°C	93.4°C																																																																													
2	LOW TEMPERATURE TURN ON TEST	NO DAMAGE 1 HOUR ( MIN )	I/P : 528VAC / 180VAC O/P : FULL LOAD Ta : -45.0°C	TEST : OK																																																																												
3	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL 60°C NO DAMAGE	I/P : 528VAC O/P : FULL LOAD Ta : 60°C HUMIDITY= 95.0% RH	TEST : OK																																																																												
4	TEMPERATURE	±0.03% /°C(0~60°C)	I/P : 347VAC	±0.01% /°C(0~60°C)																																																																												



7	COEFFICIENT	O/P : FULL LOAD	
5	STORAGE TEMPERATURE TEST	1. Thermal shock Temperature : -45°C ~ +90°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 5 CYCLE 5. Input/Output condition : STATIC	TEST : OK
6	THERMAL SHOCK TEST	1. Thermal shock Temperature : -45°C ~ 65°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 16 CYCLE 5. Input/Output condition : 230V Full Load AC ON/OFF to turn on 3sec ; turn off 1sec @ 15cycle Full Load burn in @ 1cycle	TEST : OK
7	VIBRATION TEST	1 Carton & 1 Set (1) Waveform : Sine Wave (2) Frequency : 10~500Hz (4) Acceleration : 5G (5) Test Time : 72min in each axis (X.Y.Z) (6) Ta : 25°C	TEST : OK
8	CAPACITOR LIFE CYCLE	HVG-240-24 : SUPPOSE C102 IS THE MOST CRITICAL COMPONENT (1) I/P : 347VAC O/P : FULL LOAD Ta= 25°C LIFE TIME (2) I/P : 347VAC O/P : FULL LOAD Ta= 60°C LIFE TIME (3) I/P : 347VAC O/P : 75% LOAD Ta= 60°C LIFE TIME (4) I/P : 347VAC O/P : 50% LOAD Ta= 60°C LIFE TIME	(1). 288585 HRS (2). 29688 HRS (3). 47188 HRS (4). 84252 HRS
9	MTBF	MIL-HDBK-217F NOTICE 2 STRESS ANALYSIS TOTAL FAILURE RATE : 114.5 KHRS (Ta=25°C)	
10	DMTBF / Accelerated Life test	Demonstration Mean Time Between Failure (Expected Life) : 50,000 hours @ Tcase 70°C	

TEST RESULT	TESTER	REVIEW	APPROVAL
PASS	DANIEL GAO	SANFORD SU	VINCENT ZENG