

MODEL : NSD15-12S15

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	RIPPLE & NOISE	V1: 75 mVp-p (Max)	I/P: 12VDC O/P:FULL LOAD Ta:25°C	V1: 25 mVp-p (Max)	P
2	OUTPUT VOLTAGE TOLERANCE	V1: 2 % - -2 % (Max)	I/P: 9.4VDC / 36VDC O/P:FULL / 10% LOAD Ta:25°C	V1: 0.08 % - -0.08 %	P
3	LINE REGULATION	V1: 1% - -1 % (Max)	I/P: 9.4VDC ~ 36VDC O/P:FULL LOAD Ta:25°C	V1: 0.08 % - -0.08 %	P
4	LOAD REGULATION	V1: 1 % - -1 % (Max)	I/P: 12VDC O/P:FULL ~10% LOAD Ta:25°C	V1: 0.08 % - -0.08 %	P
5	OVER/UNDERSHOOT TEST	< ±5%	I/P: 12 VDC O/P:FULL LOAD Ta:25°C	TEST: <5 %	P
6	DYNAMIC LOAD	V1: 1500 mVp-p	I/P: 12VDC O/P:FULL /Min LOAD 90%DUTY/1KHZ Ta:25°C	512 mVp-p	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	INPUT VOLTAGE RANGE	9.4VDC~ 36 VDC	I/P:TESTING O/P:FULL LOAD Ta:25°C	7.1 V~36 V	P
			I/P: LOW-LINE-0.2V= 9.2 V HIGH-LINE+5%= 37.8 V O/P:FULL/MIN LOAD ON: 30 Sec . OFF: 30 Sec 10MIN (AC POWER ON/OFF NO DAMAGE)	TEST: OK	
2	EFFICIENCY	81 % (TYP)	I/P: 12 VDC O/P:FULL LOAD Ta:25°C	82.4 %	P
3	INPUT CURRENT	12 VDC / 1.8A (TYP)	I/P: 12 VDC O/P:FULL LOAD Ta:25°C	I = 1.47 A	P
4	SHUTDOWN IDLE CURRENT	20 mA / 12VDC	I/P: 12 VDC O/P:FULL LOAD Ta:25°C	17.5 mA / 12VDC	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	Above 105%	I/P: 12VDC O/P: TESTING Ta: 25°C	171 %/12V Over power Limiting, recovers automatically after fault condition is removed	P
2	OVER VOLTAGE PROTECTION	CH1: 17.25V - 22.5V	I/P: DC SOURCE O/P: MIN LOAD Ta: 25°C	18.7 V / CH1/ 0.05A Recovers automatically after fault condition is removed	P
4	SHORT PROTECTION	SHORT EVERY OUTPUT 60 SECOND NO DAMAGE	I/P: 36 VDC O/P: FULL LOAD Ta: 25°C	NO DAMAGE Constant Current Limiting	P

CONTROL FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	REMOTE CONTROL	Logic "1" OPEN : ON Logic "0" GON : OFF	I/P: 12VDC O/P: FULL LOAD Ta: 25°C	Logic "1" : POWER ON Logic "0" : POWER OFF	P

ENVIRONMENT TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT																																																							
1	TEMPERATURE RISE TEST	MODEL : NSD15-12S5 1. ROOM AMBIENT BURN-IN : 1.5 HRS I/P: 12 VDC O/P: FULL LOAD Ta= 23°C 2. HIGH AMBIENT BURN-IN : 2 HRS I/P: 12 VDC O/P: FULL LOAD Ta= 61.9°C			P																																																							
		<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>P/N</th> <th>ROOM AMBIENT Ta= 23°C</th> <th>HIGH AMBIENT Ta= 61.9°C</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>L100</td> <td>TS026</td> <td>70.8°C</td> <td>105.1°C</td> </tr> <tr> <td>2</td> <td>T1 COIL</td> <td>147PE5151</td> <td>82.7°C</td> <td>117.5°C</td> </tr> <tr> <td>3</td> <td>Q2</td> <td>CEU1012 10A/120V</td> <td>88.1°C</td> <td>124.0°C</td> </tr> <tr> <td>4</td> <td>L1</td> <td>1.4UH 0503</td> <td>81.1°C</td> <td>116.5°C</td> </tr> <tr> <td>5</td> <td>Q1</td> <td>BCX56 1A/80V</td> <td>77.8°C</td> <td>112.6°C</td> </tr> <tr> <td>6</td> <td>U1</td> <td>TL3843D</td> <td>83.0°C</td> <td>116.2°C</td> </tr> <tr> <td>7</td> <td>C106</td> <td>100U/10V 125°C</td> <td>71.4°C</td> <td>105.1°C</td> </tr> <tr> <td>8</td> <td>D101</td> <td>MBRD660CT 6A/60V</td> <td>77.9°C</td> <td>111.9°C</td> </tr> <tr> <td>9</td> <td>D100</td> <td>6CWQ04FN 7A/40V</td> <td>79.2°C</td> <td>112.9°C</td> </tr> <tr> <td>10</td> <td>CASE</td> <td>上方中間處</td> <td>74.0°C</td> <td>108.2°C</td> </tr> </tbody> </table>	NO	Position		P/N	ROOM AMBIENT Ta= 23°C	HIGH AMBIENT Ta= 61.9°C	1	L100	TS026	70.8°C	105.1°C	2	T1 COIL	147PE5151	82.7°C	117.5°C	3	Q2	CEU1012 10A/120V	88.1°C	124.0°C	4	L1	1.4UH 0503	81.1°C	116.5°C	5	Q1	BCX56 1A/80V	77.8°C	112.6°C	6	U1	TL3843D	83.0°C	116.2°C	7	C106	100U/10V 125°C	71.4°C	105.1°C	8	D101	MBRD660CT 6A/60V	77.9°C	111.9°C	9	D100	6CWQ04FN 7A/40V	79.2°C	112.9°C	10	CASE	上方中間處	74.0°C	108.2°C		
NO	Position	P/N	ROOM AMBIENT Ta= 23°C	HIGH AMBIENT Ta= 61.9°C																																																								
1	L100	TS026	70.8°C	105.1°C																																																								
2	T1 COIL	147PE5151	82.7°C	117.5°C																																																								
3	Q2	CEU1012 10A/120V	88.1°C	124.0°C																																																								
4	L1	1.4UH 0503	81.1°C	116.5°C																																																								
5	Q1	BCX56 1A/80V	77.8°C	112.6°C																																																								
6	U1	TL3843D	83.0°C	116.2°C																																																								
7	C106	100U/10V 125°C	71.4°C	105.1°C																																																								
8	D101	MBRD660CT 6A/60V	77.9°C	111.9°C																																																								
9	D100	6CWQ04FN 7A/40V	79.2°C	112.9°C																																																								
10	CASE	上方中間處	74.0°C	108.2°C																																																								
2	OVER LOAD BURN-IN TEST	NO DAMAGE 1 HOUR (MIN)	I/P: 12 VDC O/P: 120 % LOAD Ta:25°C	TEST : OK	P																																																							
3	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOUR	I/P: 12VDC O/P: 100% LOAD Ta= -25°C	TEST : OK	P																																																							
4	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL 60 °C NO DAMAGE	I/P: 39 VDC O/P:FULL LOAD Ta= 60 °C HUMIDITY= 95 %R.H	TEST : OK	P																																																							
5	TEMPERATURE COEFFICIENT	± 0.03 %(0-60°C)	I/P: 12 VDC O/P:FULL LOAD	± 0.001 %(0-60°C)	P																																																							
6	VIBRATION TEST	1 Carton & 1 Set (1) Waveform: Sine Wave (2) Frequency:10-500Hz (3) Sweep Time:10min/sweep cycle (4) Acceleration:2G (5) Test Time:1 hour in each axis (X.Y.Z) (6) Ta:25°C		TEST : OK	P																																																							

SAFETY TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P: 1.5KVDC/min	I/P-O/P: 1.8KVDC/min Ta:25°C	I/P-O/P: 0.002 mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ	I/P-O/P: 500 VDC Ta:25°C / 70% RH	I/P-O/P: 30 GΩ NO DAMAGE	P
3	APPROVAL	TUV: Certificate NO : UL: File NO : E183223			P



E.M.C TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	RADIATION	EN55022 CLASS B	I/P: 12VDC O/P: FULL LOAD Ta: 25°C	PASS Test by certified Lab	P
2	E.S.D	EN61000-4-2 LIGHT INDUSTRY AIR: 8KV / Contact: 4KV	I/P: 12 VDC O/P: FULL LOAD Ta: 25°C	CRITERIA A	P
3	E.F.T	EN61000-4-4 LIGHT INDUSTRY INPUT: 1KV	I/P: 12 VDC O/P: FULL LOAD Ta: 25°C	CRITERIA A	P
7	Test by certified Lab & Test Report Prepare				

M.T.B.F & LIFE CYCLE CALCULATION

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	MTBF	MIL-HDBK-217F NOTICES2 PARTS COUNT TOTAL FAILURE RATE: 1734K HRS			P

COMPONENT STRESS TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	Power Transistor (D to S) or (C to E) Peak Voltage	Q2 Rated CUE1012 : 120 V 10 A	I/P: High-Line +3V = 39 V O/P: (1) Full Load Turn on (2) Output Short Ta: 25°C	(1) 90 V (2) 94 V	P
2	Diode Peak Voltage	D100 Rated STPS10170CB : 10A/170V	I/P: High-Line +3V = 39 V O/P: (1) Full Load Turn on (2) Output Short Ta: 25°C	(1) 126 V (2) 37 V	P
3	Input Capacitor Voltage	C5 Rated : 105 / 50V	I/P: High-Line +3V = 39 V O/P: (1) Full Load Turn on /Off (2) Min load Turn on /Off (3) Full Load /Min load Change Ta: 25°C	(1) 39 V (2) 39 V (3) 39 V	P
4	Control IC Voltage Test	U1 Rated TL3843D : 20 V	I/P: High-Line +3V = 39 V O/P: (1) Full Load Turn on /Off (2) Min load Turn on /Off (3) Full Load /Min load Change Ta: 25°C	(1) 11.09 V (2) 10.55 V (3) 11.09 V	P

DATE	SAMPLE	TEST RESULT	TESTER	APPROVAL
2007/2/16	RD SAMPLE	PASS	VINCENT TSENG	MAX LIN
2007/5/7	PRODUCT SAMPLE W0703C68	PASS	VINCENT TSENG	MAX LIN

2003/12/12 A50-F023