

MODEL : RPS-75-5

### OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	RIPPLE & NOISE	V1: 80 mVp-p (Max)	I/P: 230VAC O/P:FULL LOAD Ta:25°C	V1: 11 mVp-p (Max)	P
2	OUTPUT VOLTAGE ADJUST RANGE	CH1: 4.75V- 5.5V	I/P: 230 VAC I/P: 115 VAC O/P:MIN LOAD Ta:25°C	4.65 V- 5.96 V/ 230 VAC 4.65 V- 5.96 V/ 115 VAC	P
3	OUTPUT VOLTAGE TOLERANCE	V1: 2 %- -2 % (Max)	I/P: 100VAC / 264 VAC O/P:FULL/ MIN LOAD Ta:25°C	V1: 1.1 %- -1.1 %	P
4	LINE REGULATION	V1: 0.5 %- -0.5 % (Max)	I/P: 100VAC ~ 264 VAC O/P:FULL LOAD Ta:25°C	V1: 0.12 %- -0.12 %	P
5	LOAD REGULATION	V1: 1.5 %- -1.5 % (Max)	I/P: 230 VAC O/P:FULL ~MIN LOAD Ta:25°C	V1: 1 %- -1 %	P
6	SET UP TIME	230VAC: 500 ms (Max) 115 VAC: 500 ms (Max)	I/P: 230 VAC I/P: 115 VAC O/P:FULL LOAD Ta:25°C	230VAC/ 310 ms 115VAC/ 285 ms	P
7	RISE TIME	230VAC: 30 ms (Max) 115VAC: 30 ms (Max)	I/P: 230 VAC I/P: 115 VAC O/P:FULL LOAD Ta:25°C	230VAC/ 5 ms 115VAC/ 5 ms	P
8	HOLD UP TIME	230VAC: 80 ms (TYP) 115VAC: 20 ms (TYP)	I/P: 230 VAC I/P: 115 VAC O/P:FULL LOAD Ta:25°C	230VAC/ 104.7 ms 115VAC/ 21.7 ms	P
9	OVER/UNDERSHOOT TEST	< ±5%	I/P: 230 VAC O/P:FULL LOAD Ta:25°C	TEST: <5 %	P
10	DYNAMIC LOAD	V1: 1000 mVp-p	I/P: 230 VAC O/P:FULL /Min LOAD 90%DUTY/1KHZ Ta:25°C	595 mVp-p	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	INPUT VOLTAGE RANGE	90VAC~264 VAC	I/P:TESTING O/P:FULL LOAD Ta:25°C	54V~264V	P
			I/P: LOW-LINE-3V= 87 V HIGH-LINE+15%=300 V O/P:FULL/MIN LOAD ON: 30 Sec . OFF: 30 Sec 10MIN ( AC POWER ON/OFF NO DAMAGE )	TEST: OK	
2	INPUT FREQUENCY RANGE	47HZ ~63 HZ NO DAMAGE OSC	I/P: 90VAC ~ 264 VAC O/P:FULL~MIN LOAD Ta:25°C	TEST: OK	P
3	EFFICIENCY	78% (TYP)	I/P: 230 VAC O/P:FULL LOAD Ta:25°C	78%	P
4	INPUT CURRENT	230V/ 1 A (TYP)	I/P: 230 VAC I/P: 115 VAC O/P:FULL LOAD Ta:25°C	I = 0.76 A/ 230 VAC	P
		115V/ 1.5 A (TYP)		I = 1.34 A/ 115 VAC	
5	INRUSH CURRENT	230V/ 50 A (TYP)	I/P: 230 VAC I/P: 115 VAC O/P:FULL LOAD Ta:25°C	I = 40 A/ 230 VAC	P
		115V/ 25 A (TYP) COLD START		I = 20 A/ 115 VAC	
6	LEAKAGE CURRENT	< 150 uA/ 264 VAC for earth leakage current	I/P: 264 VAC O/P:Min LOAD Ta:25°C	L-FG: 119 uA N-FG: 119 uA	P
		< 100 uA/264 VAC for touch leakage current		I/P: 264 VAC O/P:Min LOAD Ta:25°C	L-V+ : 84 uA L-V-: 84 uA N-V+: 84 uA N-V-: 84 uA

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	140%~ 180 %	I/P: 230 VAC I/P: 115 VAC O/P:TESTING Ta:25°C	158 %/ 230 VAC 157%/ 115 VAC Hiccup Mode	P
2	OVER VOLTAGE PROTECTION	CH1: 5.75 V~ 6.75 V	I/P: 230 VAC I/P: 115 VAC O/P:MIN LOAD Ta:25°C	6.5V/ 230 VAC 6.5V/ 115 VAC Shunt down Re- power ON	P
3	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P: 264 VAC O/P:FULL LOAD Ta:25°C	NO DAMAGE Hiccup Mode	P

### CONTROL FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	No load power consumption	<0.75W	I/P: 240 VAC O/P:NO LOAD	0.61W/240VAC	P
2	Remote sense	>0.3V	I/P: 230 VAC O/P:FULL LOAD Ta:25°C	> 0.3V	P

### ENVIRONMENT TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT																																																																						
1	TEMPERATURE RISE TEST	MODEL : RPS-75-5 WITH FAN 1. ROOM AMBIENT BURN-IN : 1HRS I/P: 230VAC O/P: FULL LOAD Ta= 31 °C 2. HIGH AMBIENT BURN-IN : 2.5 HRS I/P: 230VAC O/P: FULL LOAD Ta= 60.7 °C			P																																																																						
		<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>P/N</th> <th>ROOM AMBIENT Ta= 31°C</th> <th>HIGH AMBIENT Ta= 60.7 °C</th> </tr> </thead> <tbody> <tr><td>1</td><td>LF2</td><td>TR-719</td><td>52.7°C</td><td>82.3°C</td></tr> <tr><td>2</td><td>BD1</td><td>US4K80 4A/800V SHI</td><td>49.1°C</td><td>78.4°C</td></tr> <tr><td>3</td><td>C6</td><td>100U/400V NCC 105°C</td><td>38.6°C</td><td>67.6°C</td></tr> <tr><td>4</td><td>C36</td><td>100U/50V NCC 105°C KY</td><td>47.3°C</td><td>76.8°C</td></tr> <tr><td>5</td><td>T1 COIL</td><td>TF-1532 JSI</td><td>65.2°C</td><td>93.7°C</td></tr> <tr><td>6</td><td>Q1</td><td>STP9NK70ZFP 7.5A/700V</td><td>31.0°C</td><td>81.1°C</td></tr> <tr><td>7</td><td>ZD1</td><td>P6KE300A LT</td><td>65.6°C</td><td>96.5°C</td></tr> <tr><td>8</td><td>D1</td><td>UF5408 3A/1KV</td><td>55.3°C</td><td>85.1°C</td></tr> <tr><td>9</td><td>D100</td><td>YG838C04R 30A/40V FUJI</td><td>63.3°C</td><td>90.3°C</td></tr> <tr><td>10</td><td>C107</td><td>2200U/16V RUB 105°C ZLH</td><td>48.5°C</td><td>77.1°C</td></tr> <tr><td>11</td><td>R6</td><td>330Ω/3W R/MO</td><td>70.7°C</td><td>101.1°C</td></tr> <tr><td>12</td><td>R3</td><td>68KΩ/2W R/MO</td><td>59.9°C</td><td>83.3°C</td></tr> <tr><td>13</td><td>U1</td><td>NCP1230D165R2 ON</td><td>44.8°C</td><td>73.6°C</td></tr> </tbody> </table>	NO	Position		P/N	ROOM AMBIENT Ta= 31°C	HIGH AMBIENT Ta= 60.7 °C	1	LF2	TR-719	52.7°C	82.3°C	2	BD1	US4K80 4A/800V SHI	49.1°C	78.4°C	3	C6	100U/400V NCC 105°C	38.6°C	67.6°C	4	C36	100U/50V NCC 105°C KY	47.3°C	76.8°C	5	T1 COIL	TF-1532 JSI	65.2°C	93.7°C	6	Q1	STP9NK70ZFP 7.5A/700V	31.0°C	81.1°C	7	ZD1	P6KE300A LT	65.6°C	96.5°C	8	D1	UF5408 3A/1KV	55.3°C	85.1°C	9	D100	YG838C04R 30A/40V FUJI	63.3°C	90.3°C	10	C107	2200U/16V RUB 105°C ZLH	48.5°C	77.1°C	11	R6	330Ω/3W R/MO	70.7°C	101.1°C	12	R3	68KΩ/2W R/MO	59.9°C	83.3°C	13	U1	NCP1230D165R2 ON	44.8°C	73.6°C		
NO	Position	P/N	ROOM AMBIENT Ta= 31°C	HIGH AMBIENT Ta= 60.7 °C																																																																							
1	LF2	TR-719	52.7°C	82.3°C																																																																							
2	BD1	US4K80 4A/800V SHI	49.1°C	78.4°C																																																																							
3	C6	100U/400V NCC 105°C	38.6°C	67.6°C																																																																							
4	C36	100U/50V NCC 105°C KY	47.3°C	76.8°C																																																																							
5	T1 COIL	TF-1532 JSI	65.2°C	93.7°C																																																																							
6	Q1	STP9NK70ZFP 7.5A/700V	31.0°C	81.1°C																																																																							
7	ZD1	P6KE300A LT	65.6°C	96.5°C																																																																							
8	D1	UF5408 3A/1KV	55.3°C	85.1°C																																																																							
9	D100	YG838C04R 30A/40V FUJI	63.3°C	90.3°C																																																																							
10	C107	2200U/16V RUB 105°C ZLH	48.5°C	77.1°C																																																																							
11	R6	330Ω/3W R/MO	70.7°C	101.1°C																																																																							
12	R3	68KΩ/2W R/MO	59.9°C	83.3°C																																																																							
13	U1	NCP1230D165R2 ON	44.8°C	73.6°C																																																																							
2	OVER LOAD BURN-IN TEST	NO DAMAGE 1 HOUR ( MIN )	I/P: 230 VAC O/P: 146% LOAD Ta:25°C	TEST : OK	P																																																																						
3	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOUR	I/P: 230 VAC O/P:100 % LOAD Ta= -20°C	TEST : OK	P																																																																						
4	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST	AFTER 12 HOURS IN CHAMBER ON CONTRO 60°C NO DAMAGE	I/P: 272 VAC O/P:FULL LOAD Ta= 60 °C HUMIDITY= 95 %R.H	TEST : OK	P																																																																						
5	TEMPERATURE COEFFICIENT	± 0.03 %(0-50°C)	I/P: 230 VAC O/P:FULL LOAD	± 0.01 %(0-50°C)	P																																																																						
6	VIBRATION TEST	1 Carton & 1 Set (1) Waveform: Sine Wave (2) Frequency:10-500Hz (3) Sweep Time:10min/sweep cycle (4) Acceleration:2G (5) Test Time:1 hour in each axis (X.Y.Z) (6) Ta:25°C		TEST : OK	P																																																																						

### SAFETY TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P: 4 KVAC/min I/P-FG: 2 KVAC/min O/P-FG: 1.5 KVAC/min	I/P-O/P: 4.2 KVAC/min I/P-FG: 2.4 KVAC/min O/P-FG: 1.8 KVAC/min Ta:25°C	I/P-O/P: 2.16 mA I/P-FG: 1.67 mA O/P-FG: 1.41 mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ I/P-FG: 500VDC>100MΩ O/P-FG:500VDC>100MΩ	I/P-O/P: 500 VDC I/P-FG: 500 VDC O/P-FG: 500 VDC Ta:25°C	I/P-O/P: 30 GΩ I/P-FG: 22 GΩ O/P-FG: 23 GΩ NO DAMAGE	P
3	APPROVAL	TUV: Certificate NO : TA 50096088 UL: File NO : E227340			P

### E.M.C TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	HARMONIC	EN61000-3-2 CLASS A	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	PASS	P
2	CONDUCTION	EN55022 CLASS B	I/P: 230 VAC (50HZ) O/P:FULL/50% LOAD Ta:25°C	PASS Test by certified Lab	P
3	RADIATION	EN55022 CLASS B	I/P: 230 VAC (50HZ) O/P:FULL LOAD Ta:25°C	PASS Test by certified Lab	P
4	E.S.D	EN61000-4-2 MEDICAL AIR:15KV / Contact:8KV	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A	P
5	E.F.T	EN61000-4-4 MEDICAL INPUT: 2KV	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A	P
6	SURGE	IEC61000-4-5 MEDICAL L-N :1KV L,N-PE:2KV	I/P: 230 VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A	P
7	Test by certified Lab & Test Report Prepare				

### M.T.B.F & LIFE CYCLE CALCULATION

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	CAPACITOR LIFE CYCLE	RPS-75-5 WITH FAN : RPSUPPOSE C107 IS THE MOST CRITICAL COMPONENT I/P: 230VAC O/P:FULL LOAD Ta= 25°C LIFE TIME= 833404 HRS I/P: 230VAC O/P:FULL LOAD Ta= 60°C LIFE TIME= 79497 HRS			P
2	MTBF	MIL-HDBK-217F NOTICES2 PARTS COUNT TOTAL FAILURE RATE: 446.8K HRS			P
3	DMTBF/Accelerated Life Test	Demonstration Mean Time Between Failure : Above 30,000 hours @ TA 40°C			P

COMPONENT STRESS TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	Power Transistor ( D to S) or (C to E) <b>Peak Voltage</b>	Q1 Rated STP9NK70Z : 700V 7.5A	I/P:High-Line +3V = 267 V O/P: (1)Full Load Turn on (2) Output Short Ta:25°C	(1) 684 V (2) 680 V	P
2	Diode <b>Peak Voltage</b>	D100 Rated YG838C04R : 40V 30A	I/P:High-Line +3V = 267 V O/P: (1)Full Load Turn on (2)Output Short Ta:25°C	(1) 38 V (2) 34 V	P
3	Clamp Diode <b>Peak Voltage</b>	D1 Rated UF5408 : 1000V 3A	I/P:High-Line +3V = 267 V O/P: (1) Dynamic Load 90%Duty/1KHz Ta:25°C	(1) 650 V	P
4	<b>Input Capacitor Voltage</b>	C5 Rated :100u / 400V/ 105°C	I/P:High-Line +3V = 267 V O/P: (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change Ta:25°C	(1) 378 V (2) 384 V (3) 384 V	P
5	<b>Control IC Voltage Test</b>	U1 Rated 1230D165 : 18 V	I/P:High-Line +3V = 267 V O/P: (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change Ta:25°C	(1) 13.66 V (2) 8.93 V (3) 13.66 V	P

DATE	SAMPLE	TEST RESULT	TESTER	APPROVAL
2006/9/4	RD SAMPLE	PASS	VINCENT TSENG	MAX LIN
2006/11/9	PRODUCT SAMPLE W0610A12	PASS	VINCENT TSENG	MAX LIN
2007/1/5	PRODUCT SAMPLE W0612B06	PASS	VINCENT TSENG	MAX LIN

2003/12/12 A50-F023