



Test Report: RSD-30H-3.3

30W Reliable Railway DC-DC Converter

1. DESIGN

VERIFY

TEST

Output Function Test

Input Function Test

Protection Function Test

Component Stress Test

2. SAFETY &

E.M.C. TEST

1. DESIGN VERIFY TEST

2. OUTPUT FUNCTION TEST


NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	OUTPUT VOLTAGE TOLERANCE (Max)	V1: 2%~ -2 %	I/P: 40 VDC / 160 VDC O/P: FULL / MIN. LOAD Ta: 25°C	V1: 0.055 %~-0.027%
2	LINE REGULATION (Max)	V1: 0.5 %~ -0.5%	I/P: 40 VDC / 160 VDC O/P: FULL LOAD Ta: 25°C	V1: 0 %~ 0 %
3	LOAD REGULATION (Max)	V1: 0.5 %~ -0.5%	I/P: 110VDC O/P: FULL ~MIN LOAD Ta: 25°C	V1: 0 %~-0.1%
4	OVER/UNDERSHOOT TEST	< ±15%	I/P: 110VDC O/P: FULL LOAD Ta: 25°C	TEST: <5.251%
5	RIPPLE & NOISE (Max)	V1: 70 mVp-p	I/P: 110VDC O/P: FULL LOAD Ta: 25°C	V1: 33.4mVp-p
<div style="display: flex; justify-content: space-around;"> <div style="text-align: center;"> <p>high frequency :</p> </div> <div style="text-align: center;"> <p>low frequency :</p> </div> </div>				
6	SET UP TIME (Max)	110VDC/ 120 ms	I/P: 110VDC O/P: FULL LOAD Ta: 25°C	110VDC/25.8ms
<p>INPUT=110VDC @ FULL LOAD</p> <p>CH1 : Output Voltage CH2 : DC Input Voltage</p>				
7	RISE TIME (Max)	110VDC/ 85 ms	I/P: 110VDC O/P: FULL LOAD Ta: 25°C	110VDC/8.8ms

<p>INPUT=110VDC @ FULL LOAD</p> <p>CH1 : Output Voltage</p>			
8	HOLD UP TIME (TYP)	110VDC / 10 ms	<p>I/P: 110VDC</p> <p>O/P: FULL LOAD</p> <p>Ta:25°C</p> <p>26.4ms / full load</p>
<p>INPUT=110VDC @ FULL LOAD</p> <p>CH1 : Output Voltage CH2 : AC Input Voltage</p>			
9	DYNAMIC LOAD	V1: 990mVp-p	<p>I/P: 110VDC</p> <p>O/P:</p> <p>(1)FULL /MIN LOAD 50%DUTY / 120HZ</p> <p>(2)FULL /MIN LOAD 50%DUTY / 1KHZ</p> <p>Ta:25°C</p> <p>352mVp-p</p> <p>508mVp-p</p>
<p>FULL /MIN LOAD 50%DUTY / 120HZ</p> <p>Ch1 Pk-Pk 352mV</p>		<p>FULL /MIN LOAD 50%DUTY / 1KHZ</p> <p>Ch1 Pk-Pk 508mV</p>	


3.

4. INPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	INPUT VOLTAGE RANGE	40 VDC / 160 VDC	I/P:TESTING O/P:FULL LOAD Ta:25°C	37.9V~160 V
			I/P: LOW-LINE-0.2= 39.8 V HIGH-LINE+3V= 163 V O/P:FULL/MIN LOAD (PLEASE CHECK DERATING CURVE) ON: 30 Sec . OFF: 30 Sec 10MIN (POWER ON/OFF NO DAMAGE)	TEST : OK
2	DC CURRENT(TYP)	110VDC/ 0.23A	I/P: 110VDC O/P:FULL LOAD Ta:25°C	I=0.2065A/110VDC
3	EFFICIENCY(TYP)	87%	I/P: 110VDC O/P:FULL LOAD Ta:25°C	87.52%



4	INRUSH CURRENT(TYP)	110VDC/ 20A COLD START	I/P:110VDC O/P:FULL LOAD Ta:25°C	I=2.39A/110 VDC
---	---------------------	---------------------------	--	-----------------



- 5.
- 6.
- 7.
- 8.
- 9.

10. PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	OVER LOAD PROTECTION	105%~135 %RATED OUTPUT POWER PROTECTION TYPE : Constant current limiting, recovers automatically after fault condition is removed	I/P: 160VDC I/P: 110VDC I/P: 40VDC O/P: TESTING Ta:25°C	118.2% 118.3% 119.2% PROTECTION TYPE : Constant current limiting, recovers automatically after fault condition is removed
2	OVER VOLTAGE PROTECTION	CH: 3.8V~ 4.5 V PROTECTION TYPE : Shut down o/p voltage, re-power on to recover	I/P: 160VDC I/P: 110VDC I/P: 40VDC O/P : NO LOAD Ta:25°C	4.23V 4.23V 4.23V PROTECTION TYPE : Shut down o/p voltage, re-power on to recover
3	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P: 110VDC O/P: FULL LOAD Ta:25°C	NO DAMAGE PROTECTION TYPE : Constant current limiting, recovers automatically after fault condition is removed
4.	INPUT REVERSE	POWER OK	I/P: 110 VDC O/P: NO LOAD Ta:25°C	NO DAMAGE

11.

12. COMPONENT STRESS TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	PWM Transistor (D to S) or (C to E) Peak Voltage	Q3 Rated 500V/18A	I/P: High-Line +3V =163V DC ON/OFF VDS: O/P: (1) Full Load (2) Output Short (3) Full Load Continue Ta:25°C	VDS: (1) 336V (2) 238V (3) 250V
2	Diode Peak Voltage	Q100 Rated : 120 A/ 40 V	I/P: High-Line +3V =163V DC ON/OFF O/P: (1) Full Load (2) Output Short (3) Full Load Continue Ta:25°C	Q100: VDS: (1) 29.2V (2) 24.2V (3) 22.2V
3	Input Capacitor Voltage	C5 Rated: 27 μ / 200 V 105 °C	I/P: High-Line +3V =163V O/P: (1) Full Load input on/off (2) Min load input on /Off (3) Full Load /Min load Change (4) Full load continue Ta:25°C	(1) 165V (2) 165V (3) 164V (4) 164V
4	Control IC Voltage Test	PWM IC U1 Rated 35V 3.9V(MIN.)	I/P: High-Line +3V =163V DC ON/OFF O/P: (1) FULL LOAD (2) Output Short (3) O.L.P (4) O.V.P. Ta:25°C	(1) 14.0V (2) 10.5V (3) 10.5V (4) 13.5V

5	Clamp Diode Peak Voltage	D4 Rated : 2A/400V	I/P : High-Line +3V = 163V DC ON/OFF O/P : (1) Dynamic Load 90%Duty/1KHz (2) Full load continue Ta : 25°C	(1) 173V (2) 172V
---	--------------------------	-----------------------	--	----------------------

13.

14. SAFETY TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	WITHSTAND VOLTAGE	EN 60950-1 I/P-O/P:4KVDC/min I/P-FG:2.5KVDC/min O/P-FG:2.5KVDC/min	I/P-O/P: 4.4KVDC/min I/P-FG: 3 KVDC/min O/P-FG:3KVDC/min Ta:25°C	I/P-O/P: 1.03mA I/P-FG: 1.47mA O/P-FG: 0.78mA NO DAMAGE
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ I/P-FG: 500VDC>100MΩ O/P-FG:500VDC>100MΩ	I/P-O/P: 500 VDC I/P-FG: 500 VDC O/P-FG: 500 VDC Ta:25°C	I/P-O/P:9999 MΩ I/P-FG: 9999MΩ O/P-FG:9999MΩ NO DAMAGE
3	GROUNDING CONTINUITY	EN 60950-1 FG(PE) TO CHASSIS OR TRACE < 100 mΩ	40A / 2min Ta:25°C	18mΩ

15.

16. E.M.C TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	RADIATION	BS EN/EN55032 CLASS B	I/P: 110 VDC O/P:FULL LOAD Ta:25°C	PASS Test by certified Lab
2	CONDUCTION	BS EN/EN55032 CLASS A	I/P: 110 VDC O/P:FULL LOAD Ta:25°C	PASS Test by certified Lab
3	E.S.D	BS EN/EN61000-4-2 LIGHT INDUSTRY AIR:8KV / Contact:6KV	I/P: 110V VDC O/P:FULL LOAD Ta:25°C	CRITERIA A
4	E.F.T	BS EN/EN61000-4-4 LIGHT INDUSTRY INPUT: 2KV	I/P: 110 VDC O/P:FULL LOAD Ta:25°C	CRITERIA A
5	SURGE	BS EN/EN61000-4-5 LIGHT INDUSTRY L-N :1KV L,N-PE:2KV	I/P: 110 VDC O/P:FULL LOAD Ta:25°C	CRITERIA A
6	Test by certified Lab & Test Report Prepare			

■ RELIABILITY TEST

ENVIRONMENT TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT																																																																
2	TEMPERATURE RISE TEST	MODEL : RSD-30H-24 1. ROOM AMBIENT BURN-IN : 1HRS I/P : 110VDC O/P : FULL LOAD Ta= 18.4℃ 2. HIGH AMBIENT BURN-IN : 1HRS I/P : 110VDC O/P : FULL LOAD Ta= 53.8℃																																																																		
				<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>ROOM AMBIENT Ta= 18.4 ℃</th> <th>HIGH AMBIENT Ta= 53.8 ℃</th> </tr> </thead> <tbody> <tr><td>1</td><td>LF1</td><td>31.5℃</td><td>65.8℃</td></tr> <tr><td>2</td><td>C5</td><td>32.2℃</td><td>66.1℃</td></tr> <tr><td>3</td><td>C12</td><td>30.9℃</td><td>65.0℃</td></tr> <tr><td>4</td><td>D4</td><td>34.5℃</td><td>68.6℃</td></tr> <tr><td>5</td><td>T1</td><td>38.0℃</td><td>70.9℃</td></tr> <tr><td>6</td><td>C40</td><td>34.8℃</td><td>68.1℃</td></tr> <tr><td>7</td><td>C112</td><td>35.7℃</td><td>68.9℃</td></tr> <tr><td>8</td><td>C105</td><td>33.9℃</td><td>67.4℃</td></tr> <tr><td>9</td><td>L100</td><td>34.1℃</td><td>67.9℃</td></tr> <tr><td>10</td><td>Q100</td><td>38.2℃</td><td>71.8℃</td></tr> <tr><td>11</td><td>U101</td><td>33.4℃</td><td>67.3℃</td></tr> <tr><td>12</td><td>Q3</td><td>34.4℃</td><td>68.6℃</td></tr> <tr><td>13</td><td>Q2</td><td>31.1℃</td><td>65.3℃</td></tr> <tr><td>14</td><td>Q1</td><td>30.9℃</td><td>65.1℃</td></tr> <tr><td>15</td><td>U1</td><td>33.4℃</td><td>67.3℃</td></tr> </tbody> </table>	NO	Position	ROOM AMBIENT Ta= 18.4 ℃	HIGH AMBIENT Ta= 53.8 ℃	1	LF1	31.5℃	65.8℃	2	C5	32.2℃	66.1℃	3	C12	30.9℃	65.0℃	4	D4	34.5℃	68.6℃	5	T1	38.0℃	70.9℃	6	C40	34.8℃	68.1℃	7	C112	35.7℃	68.9℃	8	C105	33.9℃	67.4℃	9	L100	34.1℃	67.9℃	10	Q100	38.2℃	71.8℃	11	U101	33.4℃	67.3℃	12	Q3	34.4℃	68.6℃	13	Q2	31.1℃	65.3℃	14	Q1	30.9℃	65.1℃	15	U1	33.4℃	67.3℃
NO	Position	ROOM AMBIENT Ta= 18.4 ℃	HIGH AMBIENT Ta= 53.8 ℃																																																																	
1	LF1	31.5℃	65.8℃																																																																	
2	C5	32.2℃	66.1℃																																																																	
3	C12	30.9℃	65.0℃																																																																	
4	D4	34.5℃	68.6℃																																																																	
5	T1	38.0℃	70.9℃																																																																	
6	C40	34.8℃	68.1℃																																																																	
7	C112	35.7℃	68.9℃																																																																	
8	C105	33.9℃	67.4℃																																																																	
9	L100	34.1℃	67.9℃																																																																	
10	Q100	38.2℃	71.8℃																																																																	
11	U101	33.4℃	67.3℃																																																																	
12	Q3	34.4℃	68.6℃																																																																	
13	Q2	31.1℃	65.3℃																																																																	
14	Q1	30.9℃	65.1℃																																																																	
15	U1	33.4℃	67.3℃																																																																	
3	OVER LOAD BURN-IN TEST	NO DAMAGE 1 HOUR (MIN)	I/P : 110VDC O/P : 114 % LOAD Ta : 25℃	TEST : OK																																																																
4	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOUR	I/P : 110VDC/ 40VDC O/P : 100 % LOAD Ta= -40 ℃	TEST : OK																																																																
5	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL 55 ℃ NO DAMAGE	I/P : 163VDC O/P : FULL LOAD Ta= 55 ℃ HUMIDITY= 95 %R.H	TEST: OK																																																																
6	TEMPERATURE COEFFICIENT	± 0.03 %(0~50℃)	I/P : 110VDC O/P : FULL LOAD	± 0.0047 %(0~50℃)																																																																
7	STORAGE TEMPERATURE TEST	1. Thermal shock Temperature : -40℃~+85℃ 2. Temperature change rate : 25℃ / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 5 CYCLE 5. Input/Output condition : STATIC		TEST : OK																																																																
8.	THERMAL SHOCK TEST	1. Thermal shock Temperature : -45℃~+60℃ 2. Temperature change rate : 25℃ / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 10 CYCLE 5. Input/Output condition : 110VDC/Full Load DC ON/OFF TEST turn on 58sec ; turn off 2sec		TEST : OK																																																																



9	VIBRATION TEST	1 Carton & 1 Set (1) Waveform : Sine Wave (2) Frequency : 10~500Hz (3) Sweep Time : 12min/sweep cycle (4) Acceleration : 5G (5) Test Time : 60min in each axis (X.Y.Z) (6) Ta : 25°C	TEST : OK
10	CAPACITOR LIFE CYCLE	SUPPOSE C 105 IS THE MOST CRITICAL COMPONENT (1) I/P : 110VDC O/P : FULL LOAD Ta= 25°C LIFE TIME (2) I/P : 110VDC O/P : FULL LOAD Ta= 55°C LIFE TIME (3) I/P : 110VDC O/P : 75% LOAD Ta= 55°C LIFE TIME (4) I/P : 110VDC O/P : 50% LOAD Ta= 55°C LIFE TIME	(1) 1271232HRS (2) 181313HRS (3) 228420HRS (4) 246530HRS
11	MTBF	3093.5K hrs min. Telcordia SR-332 (Bellcore) ; 396.9K hrs min. MIL-HDBK-217F (25°C)	
12	DMTBF/Accelerated Life Test	Demonstration Mean Time Between Failure (Expected Life): Above 30,000 hours @ TA 55°C	

TEST RESULT	TESTER	REVIEW	APPROVAL
PASS	Frank	Gesg	Wangdz

2007/3/20 A50-S014

17.