

Model : SCW12B-05 12W
 +5V / 480~2400mA

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	OUTPUT VOLTAGE ACCURACY	-2%~+2% (Max.)	I/P: 24VDC O/P:50% LOAD Ta:25°C	+0.88%	P
2	RIPPLE & NOISE	50mVp-p (Max.)	I/P:24VDC O/P:FULL LOAD Ta:25°C	16mVp-p	P
3	LINE REGULATION	-0.5%~+0.5% (Max.)	I/P:18VDC ~36VDC O/P:FULL LOAD Ta:25°C	-0.02%~+0.02%	P
4	LOAD REGULATION	-0.5%~+0.5% (Max.)	I/P:24VDC O/P: MIN ~FULL LOAD Ta:25°C	-0.12%~+0.08%	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	INPUT VOLTAGE RANGE	18VDC~36VDC	I/P:TESTING O/P:FULL LOAD Ta:25°C	16.4VDC~36VDC	P
2	EFFICIENCY	83% (Typ.)	I/P:24VDC O/P:FULL LOAD Ta:25°C	88.02%	P
3	INPUT CURRENT	625mA FULL LOAD (Max.) 35mA NO LOAD (Typ.)	I/P:24VDC O/P:NO / FULL LOAD Ta:25°C	572mA / FULL LOAD 27mA / NO LOAD	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	110%~180% (Typ.)	I/P:24VDC O/P:TESTING Ta:25°C	143% HICCUP MODE AUTO-RECOVER	P
2	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P:36VDC O/P:SHORT Ta:25°C	NO DAMAGE HICCUP MODE AUTO-RECOVER	P

CONTROL FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	REMOTE CONTROL	POWER ON R.C ~ -Vin > 4VDC OR OPEN POWER OFF R.C ~ -Vin < 1VDC OR SHORT	I/P:24VDC O/P:FULL LOAD Ta:25°C	POWER ON : > 2.5VDC OR OPEN POWER OFF : < 2.5VDC OR SHORT	P

SAFETY TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P:1500 VDC/min	I/P-O/P:1500 VDC/min Ta:25°C	I/P-O/P: 0.002mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ	I/P-O/P:500 VDC Ta:25°C	I/P-O/P>100MΩ NO DAMAGE	P

E.M.C TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	RADIATION	EN55022 CLASS A	I/P:24VDC O/P:FULL LOAD Ta:25°C	PASS	P

DATE	SAMPLE	TEST RESULT	TESTER	APPROVAL
2009.3.13	SAMPLE (0818R)	PASS	PETER	VINCENT ZENG