



Test Report : SCW20B-15

20W DIP Package DC-DC Regulated Converter

■ DESIGN VERIFY TEST

Output Function Test
Input Function Test
Protection Function Test
Control Function Test

■ SAFETY TEST

Safety Test

■ RELIABILITY TEST

Environment Test
Other

DESIGN VERIFY TEST
OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	VOLTAGE ACCURACY	-2.0 % ~ +2.0 % (Max)	I/P:24VDC O/P:FULL LOAD Ta:25°C	+0.74 %	P
2	RIPPLE & NOISE	80 mVp-p (Max)	I/P:24VDC O/P:FULL LOAD Ta:25°C	22mV	P
3	LINE REGULATION	-0.5% ~ +0.5% (Max)	I/P:18VDC~36VDC O/P:FULL LOAD Ta:25°C	-0.01% ~ +0.01%	P
4	LOAD REGULATION	-0.5% ~ +0.5% (Max)	I/P:24VDC O/P:10% LOAD~FULL LOAD Ta:25°C	-0.04% ~ +0.05%	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	INPUT VOLTAGE RANGE	18VDC ~36VDC	I/P:TESTING O/P:FULL LOAD Ta:25°C	14.35 ~36.0 VDC	P
2	EFFICIENCY	88 % (Typ)	I/P:24VDC O/P:FULL LOAD Ta:25°C	89.00%	P
3	DC CURRENT	957 mA / FULL LOAD (Max) 25 mA / NO LOAD (Max)	I/P:24VDC O/P:NO / FULL LOAD Ta:25°C	936.5 mA / FULL LOAD 9.5 mA / NO LOAD	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	SHORT PROTECTION	CONTINUOUS	I/P:36VDC O/P:FULL LOAD Ta:25°C	HICCUP MODE AUTO-RECOVER	P
2	OVER LOAD PROTECTION	120% ~ 190%	I/P:24VDC O/P:TESTING Ta:25°C	149.0% HICCUP MODE AUTO-RECOVER	P

CONTROL FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	REMOTE CONTROL	Power on : R.C >2.5Vdc--Vin or open Power off : R.C <0.8Vdc or short (-Vin)	I/P:24VDC O/P:100% LOAD Ta:25°C	Power on : R.C>1.13Vdc or Open Power off : R.C<1.12Vdc or Short	P

SAFETY TEST

SAFETY TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P:1.5K VDC/min	I/P-O/P:1.5K VDC/min Ta:25°C	I/P-O/P: 0.002 mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ	I/P-O/P:500 VDC Ta:25°C	I/P-O/P>100MΩ NO DAMAE	P

RELIABILITY TEST

ENVIRONMENT TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT								
1	TEMPERATURE RISE TEST	1. ROOM AMBIENT BURN-IN : 8HRS I/P:24VDC O/P:FULL LOAD Ta=25°C 2. HIGH AMBIENT BURN-IN : 8HRS I/P:24VDC O/P:FULL LOAD Ta=50°C			P								
		<table border="1"> <thead> <tr> <th>NO</th> <th>Position</th> <th>1</th> <th>2</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>CASE</td> <td>59.8°C</td> <td>84.7°C</td> </tr> </tbody> </table>				NO	Position	1	2	1	CASE	59.8°C	84.7°C
NO	Position	1	2										
1	CASE	59.8°C	84.7°C										
2	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOURS	I/P:24VDC O/P: FULL LOAD Ta= -40°C	TEST : OK	P								

OTHER

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	MTBF	MIL-HDBK-217F,GB,25°C TOTAL FAILURE RATE : 4.46418 M.T.B.F : 224005.20HRS			P

TEST RESULT	TESTER	APPROVAL
PASS	ARCHEN HSIAO	VINCENT ZENG