

Model : SKA15C-033 9.9W
+3.3V / 3A

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	OUTPUT VOLTAGE ACCURACY	-2%~+2%	I/P: 48VDC O/P:50% LOAD Ta:25°C	+0.30 %	P
2	RIPPLE & NOISE	50mVp-p	I/P:48VDC O/P:FULL LOAD Ta:25°C	15 mVp-p	P
3	LINE REGULATION	-0.2%~+0.2%	I/P:36VDC ~72VDC O/P:FULL LOAD Ta:25°C	+0.00 %~ -0.03 %	P
4	LOAD REGULATION	-0.5%~+0.5%	I/P:48VDC O/P: MIN ~FULL LOAD Ta:25°C	-0.03 %~ +0.09%	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	INPUT VOLTAGE RANGE	36VDC~72VDC	I/P:TESTING O/P:FULL LOAD Ta:25°C	31.5V~72Vdc	P
2	EFFICIENCY	76% (Typ)	I/P:48VDC O/P:FULL LOAD Ta:25°C	82.757%	P
3	INPUT CURRENT	400mA FULL LOAD (Max.) 15mA NO LOAD (Typ.)	I/P:48VDC O/P:TEST Ta:25°C	250 mA / FULL LOAD 5 mA / NO LOAD	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	110%~250%(Typ)	I/P:48VDC O/P:TESTING Ta:25°C	160.0% HICCUP MODE AUTO-RECOVER	P
2	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P:72VDC O/P:FULL LOAD Ta:25°C	NO DAMAGE HICCUP MODE AUTO-RECOVER	P



SAFETY TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P:1000 VDC/min	I/P-O/P:1000 VDC/min Ta:25°C	I/P-O/P: 0.02mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>100MΩ	I/P-O/P:500 VDC Ta:25°C	I/P-O/P>100MΩ NO DAMAGE	P

DATE	SAMPLE	TEST RESULT	TESTER	APPROVAL
2008.1.9	STOCK	PASS	PETER	T.K.CHENG